



White Dune



Coast Oak



Light Sand



Claywood Oak



Traditional Oak



Weathered Oak

TECHNICAL SPECIFICATIONS

SUBJECT	MAIN PARAMETER	SPECS.
GENERAL INFORMATION		
Thickness	2.0 mm	
Wear Layer	Class 22+	
Packaging Unit	18 pieces/ box = 5.02m ²	
Plank Size	228.6 x 1219.2 x 2 mm	
Application	General domestic	
Guarantee	10 year residential	

TECHNICAL DATA		
Name	LVT (2.0/0.2mm)	
Type of flooring	Heterogeneous PVC floor covering	ISO 10582
Classification	22+	ISO 10874
Structure	Coating, wear layer(0.2mm), print film(0.07mm)	
	Base layer (1.73mm)	
Surface treatment	Coating	
Size	Deviation ≤0.15% of nominal length up to 0.5mm maximum	ISO 24342V
Squareness, mm	≤400mm deviation≤0.25; >400mm, ≤0.35>400mm, ≤0.5	ISO 24342V
Straightness, mm	≤400mm deviation≤0.25; >400mm, ≤0.35>400mm, ≤0.5	ISO 24342V
Overall thickness, mm	Average: + 0.13/-0.10mm, individual value: average +/- 0.15mm	ISO 24346V
Wear layer thickness, mm	+13%/ -10% - not exceed ±0.1mm,	ISO 24340V
Total mass per unit	+13 %	ISO 23997V
area(average)-[g/m2]	-10 %	ISO 23997V
Dimensional stability,80 °C×6h	Glued ≤±0.4% Dry-joint & glued ≤±0.25% Loose lay ≤±0.15%	ISO 23999V
Curl, 80 °C×6h	Glued ≤±8mm Dry-joint & glued ≤±2mm Loose lay ≤±1mm	ISO 23999V
Residual indentation(average)	≤0.1 mm	ISO 24343-1V
Resistance to heat Color Fastness to heat	ΔE ≤8 ave., max	ASTM F1514
Resistance to light Color Fastness to light	6 minimum / Δ E ≤8 after 300 h	ISO 105-BO2:2014,
Staining and resistance to chemicals	Class 0	ISO 26987V
Reaction to fire	Bfl-s1	EN 13501-1V
TVOC	≤ 0.5 mg/m ³	B standard
Slip resistance	≥R9	DIN 51130V
	DS	EN 13893V
Abrasion resistance	Group T	EN 660-2V
Toxicity	Non-toxic, no heavy metals	EN71-3V
Formaldehyde	E1	EN717-1
Use recycled materials or not	No	
Features	Easy-clean Wood look Durable Slip-resistant Non-toxic	
Using area	Residential Applications	

INSTALLATION & MAINTENANCE GUIDELINES

Installation	Adhere to manufactures installation parameters
Cleaning & Maintenance	Non-abrasive detergent & micro fibre mop
	Avoid excessive exposure to water
Caution	Do not expose to direct sunlight
	Refer to the back of the box for the manufacturer's installation guidelines

